

## MJS SERIES 220-400 kVA

### TECHNICAL SPECIFICATIONS



#### GENERATOR GROUP

MODEL		MJS0220	MJS0285	MJS0330	MJS0400
Stand By Power	kVA	220	285	330	400
	kW	176	228	264	320
Prime Power	kVA	200	259.1	300	363.6
	kW	160	207.3	240	290.9

#### DIESEL ENGINE

BRAND	SHANGHAI DONGFENG				
Model	SM129TD21	SM129TAD24	SMG128TAD28	SMG128TAD31	
Engine Power - Stand By	kW	206	245	280	324
Engine Power - Prime	kW	187	223	255	295
Engine Speed (rpm)		1500	1500	1500	1500
Number of Cylinder		6 - In Line	6 - In Line	6 - In Line	6 - In Line
Displacement (lt)		8.27	8.27	8.82	12.9
Bore x Stroke (mm)		114x135	114x135	114x135	135x150
Compression Rate		18:1	18:1	18:1	17:1
Governor Type		Electronic	Electronic	Electronic	Electronic
Induction		TurboCharged	TurboCharged-Intercooler	TurboCharged-Intercooler	TurboCharged-Intercooler
Combustion System		Direct Injection	Direct Injection	Direct Injection	Direct Injection
Cooling System		Water Cooled	Water Cooled	Water Cooled	Water Cooled
Lubrication Oil Capacity (lt)		30	30	30	40
Coolant Capacity (lt)		48	48	48	64
Fuel Tank Capacity (lt)		353	353	353	491
Fuel Consumption	100% of Prime Power	52	52	52	71
	75% of Prime Power	39	39	39	53
	50% of Prime Power	27	27	27	36

#### ALTERNATOR

Output Voltage (V)	400/230
Power Factor	0.8
Number of Poles	4
Frequency (Hz)	50
Voltage Regulation	±%0,5
Connection Type	Star

#### DIMENSIONS & WEIGHT

Canopy Dimensions	mm (WxDxH)	1200x3420x2260	1200x3420x2260	1200x3420x2260	1400x3700x2626,5
Canopy Weight	kg	2250	2400	2500	3450
Open Dimensions	mm (WxDxH)	1200x2800x1780	1200x2800x1780	1200x2800x1780	1400x3200x2000
Open Weight	kg	1900	1950	2100	3035

Aytemiz-Makelsan reserves the right to make changes in model, specification, color, equipment and accessories without prior notice.

N/A: These dimensions and weights may change depending upon the characteristics of the project.